

NOTES

Control is by ASACE and NOS-C&GS.
Coordinates are based on the Lambert Projection for Oregon, North Zone (NAD 83, U.S. Survey Feet).
Datum is Mean Lower Low Water. (MLLW is 3.07 feet below National Geodetic Vertical Datum at Columbia River Mile 13.2, 1947 adjustment.)
Soundings are shown in feet and indicate depths below MLLW.
Elevations are shown thus: +2, indicating height in feet above MLLW.
The MLLW plane is shown thus:
The project depth curve is shown thus:
Reference is Navigation Chart No. 18521.
River mileage conforms to the River Mile Index of the Hydrology and Hydraulics Committee, Pacific Northwest River Basin Commission, July 1972.

The information depicted on this map represents the results of surveys made on the dates indicated and can only be considered as indicating the general condition existing at that time.

■ CONDITION □ PREDREDGE □ POSTDREDGE

THE EXISTING PROJECT

provides for a channel 40 feet deep and 600 feet wide from deep water in the Columbia River Entrance at river mile 3.0 to river mile 101.4 at the Mouth of the Willamette River; and also-

provides for a turning basin 40' deep, 800 feet wide and 4250 feet long at Astoria.

COLUMBIA AND LOWER WILLAMETTE RIVERS
BELOW VANCOUVER, WASH. AND PORTLAND, OREG.

COLUMBIA RIVER
FLAVEL BAR
28 APRIL 2004

SCALE IN FEET
500 0 500 1000 1500 2000

U.S. ARMY ENGINEER DISTRICT, PORTLAND
OPERATIONS DIVISION

SUBMITTED
APPROVED

CHIEF, HYDROGRAPHIC SURVEYS
RECOMMENDED

OPERATIONS MANAGER,
CHANNELS AND HARBORS PROJECT

CHIEF, WATERWAYS MAINTENANCE SECTION
SURVEYED: HWF PLOTTED: RLR CHECKED: DRP

3

CL-9-343

DISTRIBUTION COPY