CORPS OF ENGINEERS

U.S. ARMY



THE EXISTING PROJECT

provides for a channel *27 feet deep and 300 feet wide from the Interstate Highway Bridge at river mile 106.6 to the port terminal facilities at The Dalles at river mile 189.7.

*The 27 foot channel is presently maintained at 17 feet.

LEGEND

Primary Control Point
Coordinated Survey Points
Uncoordinated Survey Points
Dredging Ranges — Front, Rear
River Mileage from Mouth
Flow Arrows — Straight, Flow, Tidal
Harbor Lines
State Boundary
Benchmarks
Gages — Staff, Recording
33 — 48 — 72000

Aids to Navigation

Lighthouses
Lights — Fixed, Flashing, Occulting, Rear, Front
Lighted Ranges
Lighted Buoys — Red, Black, Mid Channel, Junction
Unlighted Buoys — Port, Starboard
Daybeacons
Seasonal Lights and Lighted Dredging Ranges

NOTES

Control is by USACE and NOS-C&GS.
Coordinates are based on the Lambert Projection for Oregon, North Zone (NAD 83, U.S. Survey Feet).
Datum is Columbia River Datum. (CRD is 5.41 feet above National Geodetic Vertical Datum. at Columbia River Mile 134.0, 1947 adjustment.)
Soundings are shown in feet and indicate depths below CRD.
Elevations are shown thus: +2, indicating height in feet above CRD.
The CRD plane is shown thus:
The project depth curve is shown thus:
Reference is Navigation Chart No. 18531.
River mileage conforms to the River Mile Index of the Hydrology and Hydraulics Committee, Pacific Northwest River Basins Commission.

Aerial Photography taken in 2001 by U.S.G.S.

The information depicted on this map represents the results of surveys made on the dates indicated and can only be considered as indicating the general condition existing at that time.

■ CONDITION □ PREDREDGE □ POSTDREDGE

COLUMBIA RIVER BETWEEN VANCOUVER, WASH. AND THE DALLES, OREG.

COLUMBIA RIVER

FASHION REEF

16 OCTOBER 2008

SCALE IN FEET

500 0 500 1000 1500 2000

U.S. ARMY ENGINEER DISTRICT, PORTLAND
OPERATIONS DIVISION

SUBMITTED — APPROVED

RECOMMENDED — CHIEF, WATERWAYS MAINTENANCE SECTION

CHIEF, SURVEY SECTION

SURVEYED: CCW PLOTTED: MRC CHECKED: MRC

7

CL-134-62

DISTRIBUTION COPY