

NOTES

Control is by USACE and NOS-C&GS.
Coordinates are based on the Lambert Projection for Oregon, North Zone (NAD 83, U.S. Survey Feet).
Datum is Mean Lower Low Water. (MLLW is 3.51 feet below National Geodetic Vertical Datum at Columbia River Mile 8.3, 1947 adjustment.)
Soundings are shown in feet and indicate depths below MLLW.
Elevations are shown thus: +2, indicating height in feet above MLLW.
The MLLW plane is shown thus:
The project depth curve is shown thus:
Reference is Navigation Chart No. 18521.
River mileage conforms to the River Mile Index of the Hydrology and Hydraulics Committee, Pacific Northwest River Basin Commission, July 1972.

The information depicted on this map represents the results of surveys made on the dates indicated and can only be considered as indicating the general condition existing at that time.

■ CONDITION □ PREDREDGE □ POSTDREDGE

THE EXISTING PROJECT

provides for a channel 40 feet deep and 600 feet wide from deep water in the Columbia River Entrance at river mile 3.0 to river mile 101.4 at the Mouth of the Willamette River.

LEGEND

Primary Control Point
Coordinated Survey Points
Uncoordinated Survey Points
Dredging Ranges — Front
River Mileage from Mouth
Flow Arrows — Straight — Tidal
Harbor Lines
State Boundary

Benchmarks
Gages — Staff — Recording
Range — Rear — Front

Aids to Navigation

Lighthouses
Lights — Front — Rear
Lighted Ranges — Front — Rear
Lighted Buoys — Port — Starboard — Mid Channel — Junction
Unlighted Buoys — Port — Starboard
Daybeacons
Seasonal Lights and Lighted Dredging Ranges

COLUMBIA RIVER AT THE MOUTH
OREGON AND WASHINGTON

DESDEMONA SHOAL
6 MARCH 2008

SCALE IN FEET
1000 0 1000 2000 3000 4000

U.S. ARMY ENGINEER DISTRICT, PORTLAND
OPERATIONS DIVISION

SUBMITTED
APPROVED
CHIEF, WATERWAYS MAINTENANCE SECTION
RECOMMENDED
CHIEF, SURVEY SECTION
SURVEYED: HWF PLOTTED: MBL CHECKED: MBL

CL-5-481